



**REMOVAL AND RECOVERY OF PHOSPHORUS  
FROM MUNICIPAL WASTEWATER BY  
ADSORPTION COUPLED WITH CRYSTALLIZATION**

**By  
THI AN HANG NGUYEN**

**A Dissertation  
Submitted in fulfillment for the degree of  
DOCTOR OF PHILOSOPHY  
In  
Environmental Engineering**

**University of Technology, Sydney  
New South Wales, Australia**

**June 2015**

## CERTIFICATE OF ORIGINAL AUTHORSHIP

I certify that the work in this thesis has not previously been submitted for a degree nor has it been submitted as part of requirements for a degree except as fully acknowledged within the text.

I also certify that the thesis has been written by me. Any help that I have received in my research work and the preparation of the thesis itself has been acknowledged. In addition, I certify that all information sources and literature used are indicated in the thesis.

SIGNATURE OF STUDENT:

**Thi An Hang Nguyen**

DATE: 30 June 2015

## ACKNOWLEDGEMENTS

First and foremost, I would like to express the sincere gratitude to my principal supervisor, Prof. Dr. Huu Hao Ngo, for providing me with an interesting topic and helping me to overcome all challenges during my candidature. I am indebted to him for his valuable guidance and emotional supports. I also would like to thank my supervisory committee, Dr. Wenshan Guo and Dr. Tien Vinh Nguyen for their mentor supports and useful comments on this dissertation.

I gratefully acknowledge the Australian Government for awarding me the Australia Awards Scholarship. The financial support from Centre for Technology in Water and Wastewater, UTS is highly appreciated.

This project would not have been possible without substantial help of Dr. Andrzej from Sydney Olympic Park Authority, Mr. Tyrelk from Sydney Olympic Park Wastewater Treatment Plant, and Mrs. Nga from Nhu Quynh tofu and soy milk workshop. Thank you very much for providing me with municipal wastewater and okara for use in my experiments.

I would like to extend my gratitude to M.E. Johir, UTS Environmental Engineering Laboratories Manager for his patience guidance on the use of the laboratory equipment. I am grateful to Dr. Nga for her sincere help. I appreciate Lijuan for collecting samples at night and friendship. I am thankful to Son for his assistance with SEM and XRD analysis. I also would like to thank Van for preparing some illustrations. Many thanks go to Anwar, Danious, Chung, and Tanjina for their useful discussions. I am very grateful to Tram for her sincere help with binding this thesis. Thanks a lot to other fellow post-graduate colleagues at School of Civil and Environmental Engineering for making UTS a dynamic and pleasant study place.

My heartfelt thanks go to M.Sc. Quang, my husband for his help with on-site wastewater sampling, the true love and sacrifice. My warmest thanks go to Giang and Minh, my dearest daughter and son for giving me a great motivation to complete my Ph.D. study. My love and special thanks go to my parents for encouraging me to fulfill my dreams. I owe Hung, Le, De, and Sao a big "THANH YOU" for their love and emotional supports.

Thank you all for making my Ph.D. study at UTS and my stay in Australia a wonderful and enjoyable experience!

## DEDICATION

*To my dearest husband, daughter and son  
for their love and inspiration*

# TABLE OF CONTENTS

Title page	
Certificate of original authorship, i	
Acknowledgements, ii	
Dedication, iii	
Table of contents, iv	
List of tables, xi	
List of figures, xiii	
Nomenclatures, xviii	
Abbreviations, xxii	
Greek symbols, xxiii	
Abstract, xxiv	

Chapter 1	INTRODUCTION	1-8
1.1	<b>Problem statement, 2</b>	
1.1.1	Phosphate reserve depletion, 2	
1.1.2	Phosphorus related environmental concerns, 2	
1.1.3	Phosphorus removal and recovery technologies, 2	
1.1.4	Potential and challenges to MAP recovery from municipal wastewater, 3	
1.1.5	Research gaps, 4	
1.2	<b>Research hypotheses, 5</b>	
1.3	<b>Research objectives and scope, 5</b>	
1.3.1	Research objectives, 5	
1.3.2	Research scope, 5	
1.4	<b>Research significance, 6</b>	
1.5	<b>Thesis outline, 7</b>	

- 2.1    Introduction, 10**
- 2.2    Municipal wastewater characteristics and P relevant regulations, 10**
  - 2.2.1    Municipal wastewater characteristics, 10
  - 2.2.2    Phosphorus relevant regulations, 16
- 2.3    Phosphorus removal technologies, 17**
  - 2.3.1    Conventional technologies, 17
    - A. Physical methods, 17
    - B. Chemical methods, 18
    - C. Biological methods, 19
  - 2.3.2    Non-conventional technologies, 20
    - A. Magnetic separation, 20
    - B. Crystallization, 21
    - C. Ion exchange, 21
    - D. Adsorption, 21
- 2.4    Phosphorus recovery, 25**
  - 2.4.1    Drivers for phosphorus recovery, 25
  - 2.4.2    Phosphorus recovery technologies, 25
  - 2.4.3    MAP crystallization process, 30
    - A. Formation, characteristics and practical applications, 30
    - B. Factors affecting MAP crystallization, 32
    - C. Case studies on MAP recovery at full scale, 40
    - D. Economic evaluation, 44
  - 2.4.4    Barriers to phosphorus recovery, 44
- 2.5    Phosphorus removal and recovery by adsorption and crystallization using AWBs based adsorbents, 45**
  - 2.5.1    Justification of using AWBs based adsorbents for P removal, 45
  - 2.5.2    Modification of AWBs for efficient phosphorus removal, 46
    - A. Significance, 46
    - B. Metal loading method, 47
    - C. Quaternization method, 55
    - D. Other modifying methods, 58
  - 2.5.3    Process fundamentals and applications, 65

	A. Adsorption mechanisms, 65	
	B. Desorption mechanisms, 68	
	C. Factors affecting P adsorption performance, 73	
	D. P removal by AWBs based adsorbents, 78	
	E. P recovery by means of adsorption and crystallization, 82	
<b>2.6</b>	<b>Soybean by-product (okara) as a choice medium, 84</b>	
<b>2.7</b>	<b>Conclusions and research gaps, 86</b>	
2.7.1	Major findings from literature review, 86	
2.7.2	Research gaps, 88	
<b>Chapter 3</b>	<b>EXPERIMENTAL INVESTIGATIONS</b>	<b>90-109</b>
<b>3.1</b>	<b>Materials, 91</b>	
3.1.1	The soybean by-product (okara), 91	
3.1.2	The raw municipal wastewater, 91	
3.1.3	Chemical reagents, 92	
<b>3.2</b>	<b>Methods, 93</b>	
3.2.1	Development of metal loaded adsorbents, 93	
	A. Preparation of metal loaded adsorbents, 93	
	B. Selection of the potential adsorbent, 93	
	C. Effect of metal loading conditions on P uptake of ZLO, 95	
	D. Recycling of the loading metal ( $Zr^{4+}$ ) solution, 95	
	E. Characterization of the selected adsorbent (ZLO), 95	
3.2.2	Phosphorus removal in batch mode experiments, 97	
	A. Effects of process parameters, 97	
	B. Adsorption isotherm study, 99	
	C. Adsorption kinetic study, 99	
	D. Adsorption thermodynamic study, 99	
	E. Desorption and regeneration studies, 100	
	F. Calculation of the batch adsorption parameters, 100	
3.2.3	Phosphorus removal in column mode experiments, 100	
	A. Lab scale reactor, 100	
	B. Semi-pilot scale reactor, 102	
	C. Column scale-up calculations, 103	

	D. Calculation of breakthrough curve parameters, 104	
3.2.4	Recovery of phosphorus as MAP, 105	
	A. MAP synthesis, 105	
	B. Evaluation of the harvested MAP, 106	
3.2.5	Analytical methods and instruments, 107	
3.2.6	Statistical analysis, 108	
<b>3.3</b>	<b>The general experimental procedure, 109</b>	
 Chapter 4	 DEVELOPMENT OF METAL LOADED OKARA AS PHOSPHORUS ADSORBENTS	 110-129
<b>4.1</b>	<b>Introduction, 111</b>	
	4.1.1 Research background, 111	
	4.1.2 Objectives of Chapter 4, 112	
<b>4.2</b>	<b>Selection of the potential adsorbent from three developed metal loaded adsorbents, 112</b>	
	4.2.1 Phosphate adsorption capacity, 113	
	4.2.2 Desorption and regeneration abilities, 116	
	4.2.3 Metal leaching from metal loaded adsorbents during adsorption and desorption tests, 118	
	4.2.4 Selection of the best adsorbent from developed ones, 119	
<b>4.3</b>	<b>Effects of the metal loading conditions on the phosphate adsorption capacity of ZLO, 119</b>	
<b>4.4</b>	<b>Recycling of the metal loading (<math>Zr^{4+}</math>) solution, 120</b>	
<b>4.5</b>	<b>Characterization of the selected adsorbent (ZLO), 122</b>	
	4.5.1 Physical properties of ZLO, 122	
	4.5.2 Chemical properties of ZLO, 123	
	A. SEM analysis, 123	
	B. EDS analysis, 124	
	C. FTIR analysis, 125	
	D. Elemental analysis, 128	
<b>4.6</b>	<b>Conclusion, 129</b>	



Chapter 5      ADSORPTION OF PHOSPHORUS FROM      130-151  
SYNTHETIC WASTEWATER BY ZIRCONIUM  
LOADED OKARA: BATCH STUDY

- 5.1      Introduction, 131**
- 5.2      Factors affecting the batch adsorption, 132**
  - 5.2.1    Solution pH, 132
  - 5.2.2    The adsorbent dose, 134
  - 5.2.3    The adsorbent particle size, 135
  - 5.2.4    Foreign anions, 135
- 5.3      Adsorption isotherms, 137**
- 5.4      Adsorption kinetics, 144**
- 5.5      Adsorption thermodynamics, 147**
- 5.6      Desorption and regeneration studies, 149**
- 5.7      Conclusion, 150**

Chapter 6      ADSORPTION OF PHOSPHORUS FROM      152-179  
SYNTHETIC AND MUNICIPAL  
WASTEWATER BY ZIRCONIUM LOADED  
OKARA: COLUMN STUDY

- 6.1      Introduction, 153**
- 6.2      Laboratory scale bioreactor, 155**
  - 6.2.1    Removal phosphorus from synthetic solution, 155
    - A. Effect of column design parameters, 155
    - B. Breakthrough curve modeling, 162
    - C. Column adsorption capacity of ZLO, 168
  - 6.2.2    Application of ZLO in treating municipal wastewater, 170
    - A. Comparative study on adsorption performance of ZLO in synthetic and municipal wastewater, 170
    - B. Successive adsorption-desorption cycles, 171
- 6.3      Semi-pilot scale bioreactor, 174**
  - 6.3.1    Adsorption of P from municipal wastewater by ZLO, 174
  - 6.3.2    Desorption of P from ZLO, 175

**6.4 Scale-up of the column adsorption system, 177**

**6.5 Conclusion, 178**

Chapter 7      **RECOVERY OF PHOSPHORUS FROM**      180-205  
                         **MUNICIPAL WASTEWATER BY ADSORPTION**  
                         **COUPLED WITH CRYSTALLIZATION**

**7.1 Introduction, 181**

7.1.1 The significance of phosphorus removal and recovery, 181

7.1.2 The phosphorus recovery technologies, 181

7.1.3 The advantages of MAP recovery process, 181

7.1.4 Potential and challenges of P recovery from municipal wastewater, 182

7.1.5 Research gaps, 182

7.1.6 Aims and scopes, 183

**7.2 Characteristics of desorption solution, 183**

**7.3 Factors affecting the MAP recovery, 185**

7.3.1 Solution pH, 185

7.3.2 Molar ratio of Mg: N: P, 187

7.3.3 Magnesium and ammonium sources, 189

7.3.4 Reaction temperature, 191

**7.4 Evaluation of the harvested precipitates, 193**

7.4.1 Crystal characterization, 194

A. Elemental analysis, 194

B. XRD analysis, 195

C. SEM analysis, 196

D. FTIR analysis, 197

7.4.2 MAP purity evaluation, 198

7.4.3 Phosphorus bioavailability, 199

**7.5 Economic assessment, 199**

7.5.1 The cost of ZLO development, 199

7.5.2 The cost-benefits of MAP recovery, 202

**7.6 Disposal the effluent after MAP crystallization, 204**

**7.7 Conclusion, 204**

Chapter 8	CONCLUSIONS AND FUTURE RESEARCH	206-211
8.1	<b>Overall conclusion, 207</b>	
8.1.1	Major findings, 207	
8.1.2	Contributions to the field, 209	
8.2	<b>Recommendations for future research, 210</b>	
8.2.1	Evaluation of ZLO safety, 210	
8.2.2	Agronomic study of the harvested MAP, 210	
8.2.3	Alternative sources of chemicals, 210	
8.2.4	Recycling of chemicals, 210	
8.2.5	Use of ZLO for arsenate removal, 210	
8.2.6	Recovery of phosphorus from AWBs, 211	
REFERENCES		212-229
APPENDIX		230-232
CIRRICULUM VITAE		233-235

## LIST OF TABLES

No	Table title	Page
CHAPTER 2		19
<b>Table 2.1</b>	Physical and chemical characteristics of raw municipal wastewater with minor contributions of industrial wastewater (adapted from Henze and Comeau, 2008)	11
<b>Table 2.2</b>	Typical content of metals in municipal wastewater with minor contributions of industrial wastewater (adapted from Henze and Comeau, 2008)	12
<b>Table 2.3</b>	Biological characteristics of municipal wastewaters, number of microorganisms per 100 ml (adapted from Henze and Comeau, 2008)	12
<b>Table 2.4</b>	Typical effluent quality following various levels of treatment (adapted from Australian guidelines for sewerage systems - effluent management, 1997)	14
<b>Table 2.5</b>	Effluent discharge standards of different countries	16
<b>Table 2.6</b>	Summary of advantages and disadvantages of various phosphorus removal technologies	23
<b>Table 2.7</b>	P recovery potential with different products of WWTPs (adapted from Nieminen, 2010)	28
<b>Table 2.8</b>	P recovery from different products of WWTPs	29
<b>Table 2.9</b>	Optimum pH for MAP crystallization from wastewater	34
<b>Table 2.10</b>	Mg sources for MAP crystallization (adapted from Liu et al., 2013)	36
<b>Table 2.11</b>	Effect of Mg: P molar ratio on P recovery efficiency	37
<b>Table 2.12</b>	Industrial scale processes for P recovery as MAP (adapted from Nieminen, 2010)	43
<b>Table 2.13</b>	The percentage of Mg, N, P in the recovered and pure MAP (adapted from Nieminen, 2010)	44
<b>Table 2.14</b>	P adsorption performances of various metal loaded AWBs based adsorbents	53
<b>Table 2.15</b>	P adsorption performances of different quaternized AWBs based adsorbents	61
<b>Table 2.16</b>	P adsorption performances of diverse AWBs based adsorbents prepared by other modifying methods	63
<b>Table 2.17</b>	Comparison of various modification methods for development of AWBs based P adsorbents	64
<b>Table 2.18</b>	Desorption of P from spent AWBs based adsorbents	71
<b>Table 2.19</b>	The maximum phosphate adsorption capacity of natural AWBs and commercial adsorbents	79

CHAPTER 4	3
<b>Table 4.1</b>	Comparing ILO, IZLO, and ZLO with other metal loaded adsorbents in the literature in term of $\text{PO}_4^{3-}$ adsorption capacity 115
<b>Table 4.2</b>	Comparison of the P removal percentage between ZLO-1 and ZLO-2 121
<b>Table 4.3</b>	Functional groups of okara, ZLO, and P loaded ZLO 127
CHAPTER 5	3
<b>Table 5.1</b>	The maximum adsorption capacity of ZLO for $\text{PO}_4^{3-}$ in comparison with various biosorbents and commercial adsorbents 138
<b>Table 5.2</b>	Isotherm and kinetic parameters by non-linear regression method for P adsorption onto ZLO 143
<b>Table 5.3</b>	Thermodynamic parameters for P adsorption onto ZLO 148
CHAPTER 6	8
<b>Table 6.1</b>	Breakthrough curve parameters for P adsorption onto ZLO at different operating conditions 161
<b>Table 6.2</b>	Adams-Bohart, Thomas and Yoon-Nelson model constants for P adsorption onto ZLO column 166
<b>Table 6.3</b>	BDST model constants for P adsorption on ZLO 167
<b>Table 6.4</b>	Prediction of breakthrough time for different bed depths by BDST model 168
<b>Table 6.5</b>	Comparing ZLO with various adsorbents in term of the P dynamic adsorption capacity 169
<b>Table 6.6</b>	Parameters for three cycles of adsorption - desorption with raw municipal wastewater 173
<b>Table 6.7</b>	Operating conditions of the semi-pilot scale column adsorption test 174
<b>Table 6.8</b>	Proposed full-scale column parameters 178
CHAPTER 7	5
<b>Table 7.1</b>	Characteristics of the desorption solution 185
<b>Table 7.2</b>	MAP recovery from desorption solution at various conditions 193
<b>Table 7.3</b>	Elemental composition of MAP recovered from desorption solution at the optimal condition 194
<b>Table 7.4</b>	Comparison of heavy metal contents in MAP recovered from desorption solution with legal limits 195
<b>Table 7.5</b>	Comparing ZLO with other AWBs based adsorbents and commercial adsorbents in term of the cost 200

---

## LIST OF FIGURES

No	Figure caption	Page
CHAPTER 1		1
<b>Figure 1.1</b>	The main tasks and scope of this study	6
CHAPTER 2		14
<b>Figure 2.1</b>	Different forms of phosphate in municipal wastewater (modified from Bhojappa, 2009)	15
<b>Figure 2.2</b>	The principle of biological phosphorus removal process (Nieminen, 2010)	20
<b>Figure 2.3</b>	The concentrations of involving substances in biological P removal process (Nieminen, 2010)	20
<b>Figure 2.4</b>	Possible locations for P recovery in WWTPs (Nieminen, 2010)	26
<b>Figure 2.5</b>	The precipitation/crystallization technology (adapted from Cornel and Schaum, 2009)	27
<b>Figure 2.6</b>	The wet-chemical technology (adapted from Cornel and Schaum, 2009)	27
<b>Figure 2.7</b>	The thermo-chemical technology (adapted from Adam, 2011)	27
<b>Figure 2.8</b>	A. Photomicrograph of a MAP liquor (adapted from Yetilmezsoy et al., 2011), and B. SEM image of MAP recovered from dairy manure filtrate (adapted from Huchzermeier, 2011)	31
<b>Figure 2.9</b>	Methods of modifying AWBs for better P removal	48
<b>Figure 2.10</b>	Formation of exchangeable hydroxyl ions during hydrolysis, where $m = 1$ or $2$ ; $Ln$ stands for $La(III)$ , $Ce(III)$ , $Fe(III)$ (adapted from Biswas et al., 2007)	67
<b>Figure 2.11</b>	Ligand exchange reaction, where $q = 1$ or $2$ and $P$ represents phosphate anion (adapted from Biswas et al., 2007)	67
<b>Figure 2.12</b>	P recovery from wastewaters via adsorption onto AWBs based adsorbents and crystallization	83
<b>Figure 2.13</b>	Okara as a byproduct of the tofu and soymilk production processes	85
<b>Figure 2.14</b>	Image of fresh soybean by-product (okara)	85
CHAPTER 3		8
<b>Figure 3.1</b>	Collecting soybean by-product (okara) from Nhu Quynh tofu and soy milk workshop	91

<b>Figure 3.2</b>	Collecting raw municipal wastewater at Sydney Olympic Park Wastewater Treatment Plant using a refrigerated sampler	92
<b>Figure 3.3</b>	The experimental design to determine the permeability coefficient of ZLO	97
<b>Figure 3.4</b>	Design of the fixed-bed column tests: A. Lab scale mini column, and B. Semi-pilot scale big column	103
<b>Figure 3.5</b>	Analytical instruments: a) SA7 vortex mixer and b) Spectroquant <sup>®</sup> NOVA 60, Merck, Germany	107
<b>Figure 3.6</b>	Analytical instruments: a) Zeiss Evo LS15 SEM, Germany, b) IRAffinity-1 Fourier Transform Infrared Spectrophotometer, Shimadzu Corporation, Japan, and c) Siemens D5000 X-ray Diffractometer	108
<b>Figure 3.7</b>	Analytical instruments: a) 790 Personal IC, Metrohm, USA and b) 4100 MP-AES Spectrometer, Agilent Technologies, USA	108
<b>Figure 3.8</b>	Diagram of P recovery from municipal wastewater by adsorption onto ZLO coupled with crystallization as MAP	109
<b>CHAPTER 4</b>		9
<b>Figure 4.1</b>	Isotherm of P adsorption by ILO, IZLO, ZLO (Adsorbent particle size = 150-300 $\mu\text{m}$ , pH = 7.6 $\div$ 7.8, $C_i$ = 10 $\div$ 500 mg P/L, adsorbent dose = 10 g/L, shaking speed = 120 rpm, temperature = 298 K, contact time = 24 h. The standard deviation values = 0.04 $\div$ 0.52 mg/g for sample size N = 3)	113
<b>Figure 4.2</b>	The P adsorption and desorption efficiencies of non-activated ZLO and IZLO in 5 consecutive cycles ( $C_i$ = 50 mg P/L, adsorbent dose = 10 g/L, shaking speed = 120 rpm, temperature = 298 K, contact time = 24 h. The standard deviation values = 0.70 $\div$ 3.49% for sample size N = 3)	117
<b>Figure 4.3</b>	The P adsorption and desorption efficiencies of activated ZLO and IZLO in 5 consecutive cycles ( $C_i$ = 50 mg P/L, adsorbent dose = 10 g/L, shaking speed = 120 rpm, temperature = 298 K, contact time = 24 h. The standard deviation values = 0.29 $\div$ 3.97% for sample size N = 3)	118
<b>Figure 4.4</b>	Effect of metal loading conditions on the P uptake of ZLO (ZLO particle size = 300-425 $\mu\text{m}$ , pH = 7 $\div$ 7.5, $C_i$ = 10 $\div$ 500 mg P/L, ZLO dose = 10 g/L, shaking speed = 120 rpm, temperature = 298 K, contact time = 24 h. The standard deviation values = 0.04-0.98 mg/g for sample size N = 3)	120
<b>Figure 4.5</b>	Comparison of the P removal percentage of ZLO prepared with $\text{Zr}^{4+}$ recycled up to 10 times (The standard deviation values = 0.35-1.19% for sample size N = 3)	122
<b>Figure 4.6</b>	Particle size distribution of ZLO (The standard deviation values = 0.07-0.88% for sample size N = 3)	123

<b>Figure 4.7</b>	SEM images of a) raw okara and b) zirconium loaded okara (ZLO)	123
<b>Figure 4.8</b>	EDS spectra of a) natural okara, b) ZLO, and c) phosphorus loaded ZLO	125
<b>Figure 4.9</b>	FTIR spectra of NSB) natural okara, 2B) ZLO before P adsorption, and 2A) ZLO after P adsorption	128
<b>CHAPTER 5</b>		10
<b>Figure 5.1</b>	Effect of the solution pH on P adsorption onto ZLO ( $C_i = 50$ mg P/L, ZLO dose = 10 g/L, shaking speed = 120 rpm, contact time = 24 h, temperature = 25 °C. The standard deviation values = 0.05-1.16% for sample size $N = 3$ )	133
<b>Figure 5.2</b>	Effect of biosorbent dose on P adsorption onto ZLO ( $C_i = 5, 10, 25, 50$ mg P/L, shaking speed = 120 rpm, contact time = 24 h, temperature = 25 °C, ZLO dose = 1, 2, 3, 5, 7, 10, 12 g/L)	134
<b>Figure 5.3</b>	Effect of the biosorbent particle size on P removal percentage of ZLO ( $C_i = 50, 100, 200, 300, 400, 500, 600$ mg P/L, ZLO dose = 10 g/L, shaking speed = 120 rpm, temperature = 298 K, contact time = 24 h. The standard deviation values = 0.45-2.12% for sample size $N = 3$ )	135
<b>Figure 5.4</b>	Effect of the competing anions on P adsorption onto ZLO ( $C_i = 100$ mg P/L, ZLO dose = 20 g/L, contact time = 24 h, shaking speed = 120 rpm, reaction temperature = 298 K)	137
<b>Figure 5.5</b>	The fitting of isotherm models to P adsorption onto ZLO (biosorbent particle size = 150-1000 $\mu\text{m}$ , pH = 7 $\div$ 7.5, $C_i = 10\div 500$ mg P/L, ZLO dose = 10 g/L, contact time = 24 h, shaking speed = 120 rpm, reaction temperature = 298 K. The standard deviation values = 0.10-0.67 mg/g for sample size $N = 3$ )	141
<b>Figure 5.6</b>	Kinetic curves of P adsorption onto ZLO at different initial P concentrations and a given ZLO dose	144
<b>Figure 5.7</b>	Kinetic curves of P adsorption onto ZLO at different initial P concentrations and optimal ZLO doses	145
<b>Figure 5.8</b>	The fitting of kinetic models to P adsorption onto ZLO ( $C_i = 50$ mg P/L, ZLO dose = 10 g/L, shaking speed = 120 rpm, temperature = 298 K. The standard deviation values = 0.08-0.21 mg/g for sample size $N = 3$ )	147
<b>Figure 5.9</b>	Thermodynamic analysis for P adsorption onto ZLO ( $C_i = 10\div 500$ mg P/L, ZLO dose = 10 g/L, shaking speed = 120 rpm, contact time = 24 h, temperature = 298, 308, 318 K): A plot of $\ln(q_e/C_e)$ versus $q_e$	148



<b>Figure 5.10</b>	Comparison of adsorption/desorption efficiencies after 5 consecutive cycles between non-activated ZLO and activated ZLO (The standard deviation values = 0.29-2.76% for sample size N = 3)	150
<b>CHAPTER 6</b>		11
<b>Figure 6.1</b>	Effect of flow rate on the breakthrough curve of P adsorption onto ZLO (natural pH, particle size = 1 mm-600 $\mu$ m, $C_i$ = 5.5 mg P/L, bed height = 23 cm)	156
<b>Figure 6.2</b>	Effect of influent P concentration on the breakthrough curve of P adsorption onto ZLO (natural pH, particle size = 1 mm-600 $\mu$ m, flow rate = 12 mL/min, bed height = 23 cm)	157
<b>Figure 6.3</b>	Effect of bed height on the breakthrough curves of P adsorption onto ZLO (natural pH, particle size = 1 mm-600 $\mu$ m, flow rate = 12 mL/min, $C_i$ = 5.5 mg P/L)	158
<b>Figure 6.4</b>	Effect of pH on the breakthrough curve of P adsorption on ZLO (bed height = 23 cm, flow rate = 12 mL/min, influent P concentration = 5.6 mg/L, and particle size = 1 mm-600 $\mu$ m)	159
<b>Figure 6.5</b>	Effect of particle size on the breakthrough curve of P adsorption onto ZLO (natural pH, bed heights = 11.5 cm and 9 cm, flow rate = 12 mL/min, influent P concentration = 5.5 mg/L)	160
<b>Figure 6.6</b>	BDST model for 10%, 30%, 50%, and 90% breakthrough at different bed depths and constant inlet P concentration (5.5 mg/L) and flow rate (12 mL/min)	164
<b>Figure 6.7</b>	Breakthrough curves for P adsorption from synthetic and raw municipal wastewater by ZLO (Particle size >600 $\mu$ m; bed depth = 21 cm, flow rate = 28 mL/min, inlet P concentration = 5.7 mg/L)	170
<b>Figure 6.8</b>	Breakthrough curves for P adsorption from municipal wastewater by ZLO in three cycles ( $C_i$ = 6.0 mg P/L, flow rate = 12 mL/min, bed depth = 10 cm, and particle size = 1mm-600 $\mu$ m)	172
<b>Figure 6.9</b>	The performance of ZLO packed bed column in three successive cycles of adsorption - desorption (The standard deviation values = 0.86-1.77% for sample size N = 3)	173
<b>Figure 6.10</b>	Breakthrough curve for P adsorption from municipal wastewater on ZLO column at semi-pilot scale (100 g ZLO; bed depth = 30 cm, flow rate = 53 mL/min, $C_i$ = 5.5 mg P/L)	175
<b>Figure 6.11</b>	Desorption profile of ZLO column (100 g ZLO, desorption solution = 0.2 M NaOH, flow rate = 13.25 mL/min)	177
<b>CHAPTER 7</b>		16
<b>Figure 7.1</b>	Effect of pH on the MAP crystallization from desorption solution ( $C_i$ = 139 mg P/L, Mg: N: P molar ratio = 2:2:1, 120	186

	rpm, room temperature)	
<b>Figure 7.2</b>	SEM images of MAP recovered from P desorption solution at various pH conditions: a) pH = 9, and b) pH = 10	187
<b>Figure 7.3</b>	Effect of Mg: N: P molar ratio on the MAP crystallization from desorption solution (pH = 9, $C_i$ = 156 mg P/L, stirring speed = 120 rpm, reaction temperature = 22 °C, $\text{NH}_4\text{Cl}$ + $\text{MgCl}_2 \cdot 6\text{H}_2\text{O}$ )	188
<b>Figure 7.4</b>	SEM images of MAP recovered from P desorption solution at different Mg: N: P molar ratios: a) 1:1:1, and b) 2:2:1	189
<b>Figure 7.5</b>	Effect of magnesium and ammonium sources on MAP recovery from desorption solution: A. $\text{NH}_4\text{Cl}$ + $\text{MgCl}_2 \cdot 6\text{H}_2\text{O}$ , B. $(\text{NH}_4)_2\text{SO}_4$ + $\text{MgSO}_4$ (pH = 9, Mg: N: P molar ratio = 2:2:1, $C_i$ = 189 mg P/L, stirring speed = 120 rpm, reaction temperature = 22 °C)	190
<b>Figure 7.6</b>	SEM images of MAP recovered from desorption solution using different magnesium and ammonium sources: a) $\text{NH}_4\text{Cl}$ + $\text{MgCl}_2 \cdot 6\text{H}_2\text{O}$ , and b) $(\text{NH}_4)_2\text{SO}_4$ + $\text{MgSO}_4 \cdot 7\text{H}_2\text{O}$	190
<b>Figure 7.7</b>	Effect of solution temperature on MAP crystallization from desorption solution (pH = 9, Mg: N: P molar ratio = 2:2:1, $C_i$ = 171.6 mg P/L, stirring speed = 120 rpm, $\text{NH}_4\text{Cl}$ + $\text{MgCl}_2 \cdot 6\text{H}_2\text{O}$ )	192
<b>Figure 7.8</b>	SEM images of MAP recovered from desorption solution at varying solution temperatures: a) 8°C, and b) 22°C	192
<b>Figure 7.9</b>	MAP recovered from municipal wastewater by adsorption onto ZLO	193
<b>Figure 7.10</b>	XRD pattern of MAP recovered from desorption solution at the optimal crystallization condition	195
<b>Figure 7.11</b>	SEM image of MAP recovered from desorption solution at the optimal crystallization condition	197
<b>Figure 7.12</b>	FTIR spectrum of MAP recovered from desorption solution at the optimal crystallization condition	198
<b>Figure 7.13</b>	Comparing the recovered MAP with the synthetic MAP in term of price (based on analytical grade chemical prices)	201
<b>Figure 7.14</b>	Components of the recovered MAP price (based on analytical grade chemical prices)	201
<b>Figure 7.15</b>	Comparing the recovered MAP with the synthetic MAP in term of price (based on industrial grade chemical prices)	203
<b>Figure 7.16</b>	Components of the recovered MAP price (based on industrial grade chemical prices)	204

---

## NOMENCLATURES

Symbol	Description	Unit
A	Bed cross-sectional area	cm <sup>2</sup>
Å	Angstrom	
AER	Adsorbent exhaustion rate	g/L
Al <sup>3+</sup>	Aluminum (III) ion	
As	Arsenic	
BOD <sub>5</sub>	Biochemical oxygen demand after 5 days	mg/L
BV	Bed volume	cm <sup>3</sup>
C <sub>b</sub>	Phosphorus concentration at breakthrough time	mg/L
C <sub>o</sub>	Initial concentration of phosphorus	mg/L
C <sub>t</sub>	Concentration of phosphorus at time t	mg/L
Ca <sup>2+</sup>	Calcium ion	
CaCO <sub>3</sub>	Calcium carbonate	
CaO	Calcium oxide	
Ca(OH) <sub>2</sub>	Calcium hydroxide	
Ca <sub>3</sub> (PO <sub>4</sub> ) <sub>2</sub>	Tricalcium phosphate	
Cd	Cadmium	
Cl <sup>-</sup>	Chloride ion	
ClO <sub>4</sub> <sup>-</sup>	Perchlorate ion	
CO <sub>2</sub>	Carbon dioxide	
CO <sub>3</sub> <sup>2-</sup>	Carbonate ion	
COD	Chemical oxygen demand	mg/L
Cu <sup>2+</sup>	Copper ion	
D	Column inner diameter	cm

DMF	N,N-dimethylformamide	
E	Activation energy	kJ/mol
EBCT	Empty bed contact time	min
EDA	Ethylene diamine triethylamine	
EDTA	Ethylene diamine tetra acetic acid	
F <sup>-</sup>	Fluoride ion	
Fe <sup>2+</sup>	Iron (II) ion	
Fe <sup>3+</sup>	Iron (III) ion	
g/L	Gram per liter	
HCl	Hydrochloric acid	
Hg	Mercury	
HNO <sub>3</sub>	Nitric acid	
H <sub>3</sub> PO <sub>4</sub>	Phosphoric acid	
H <sub>2</sub> PO <sub>4</sub> <sup>-</sup>	Di hydrogen phosphate ion	
HPO <sub>4</sub> <sup>2-</sup>	Hydrogen phosphate ion	
H <sub>2</sub> SO <sub>4</sub>	Sulfuric acid	
IS	Ionic strength	M
k <sub>AB</sub>	Adams-Bohart kinetic constant	L/mg.min
K <sub>F</sub>	Freundlich constant	(mg/g)(L/mg) <sup>1/n</sup>
K <sub>L</sub>	Langmuir constant related to the energy of adsorption	L/mg
k <sub>Th</sub>	Thomas rate constant	mL/min.mg
k <sub>YN</sub>	Yoon-Nelson rate velocity constant	1/min
KCl	Potassium chloride	
m	Mass of dry adsorbent	g
m <sup>2</sup> /g	Square meter per gram	
m <sup>3</sup>	Cubic meter	
m <sup>3</sup> /d	Cubic meter per day	
kg/d	Kilogram per day	
km <sup>3</sup>	Cubic kilometer	
m <sub>f</sub>	Mass of empty flask	
m <sub>f+w</sub>	Mass of filled volumetric flask + water	
m <sub>s+f</sub>	Mass of ZLO + volumetric flask	
m <sub>s+f+w</sub>	Mass of ZLO + volumetric flask + water	
Mg <sup>2+</sup>	Magnesium ion	
MgCl <sub>2</sub>	Magnesium chloride	
MgCl <sub>2</sub> .6H <sub>2</sub> O	Magnesium chloride hexahydrate	

$\text{MgNH}_4\text{PO}_4 \cdot 6\text{H}_2\text{O}$	Magnesium ammonium phosphate hexahydrate	
$\text{MgO}$	Magnesium oxide	
$\text{Mg}(\text{OH})_2$	Magnesium hydroxide	
$\text{MgSO}_4 \cdot 7\text{H}_2\text{O}$	Magnesium sulfate heptahydrate	
mg/L	Milligram per liter	
mg P/L	Milligram phosphorus per liter	
mg $\text{PO}_4/\text{g}$	Milligram phosphate per gram	
min	Minute	
mL/min	Milliliter per minute	
$\text{MoO}_4^{2-}$	Molybdate ion	
MPa	Mega Pascal	
MSBG	Modified sugarcane baggase	
$\mu\text{m}$	Micrometer	
$\mu\text{M}$	Micro molar	
mM	Mill molar	
Mn	Manganese	
mV	mill volt	
n	Freundlich constant	
N	Nitrogen	
NaOH	Sodium hydroxide	
$\text{Na}_2\text{HPO}_4$	Disodium hydrogen phosphate	
$\text{NaH}_2\text{PO}_4 \cdot 2\text{H}_2\text{O}$	Sodium dihydrogen orthophosphate dihydrate	
$\text{Na}_{3.25}(\text{OH})_{0.25}\text{PO}_4 \cdot 12\text{H}_2\text{O}$	Trisodium phosphate dodecahydrate	
$\text{NH}_4^+$	Ammonium ion	
$\text{NH}_4\text{Cl}$	Ammonium chloride	
$\text{Ni}^{2+}$	Nickel ion	
$\text{NO}_2^-$	Nitrite ion	
$\text{NO}_3^-$	Nitrate ion	
$\text{N}_0$	Saturation phosphorus concentration	mg/L
NTUs	Nephelometric turbidity units	
P	Phosphorus	
$\text{Pb}^{2+}$	Lead ion	
$\text{P}_s$	Particle size	mm
$\text{PO}_4^{3-}$	Phosphate ion	
Q	Volumetric flow rate	mL/min
$q_b$	Amount of phosphorus adsorbed per unit of dry	mg/g

	weight of adsorbent at breakthrough time	
$q_e$	Equilibrium adsorption capacity of the adsorbent	mg/g
$q_m$	Maximum adsorption capacity of the adsorbent	mg/g
$q_s$	Amount of phosphorus adsorbed per unit of dry weight of adsorbent at saturation time	mg/g
$q_{total}$	Total mass of phosphorus adsorbed	mg
$R_b$	Removal percentage of phosphorus at breakthrough time	%
$R_s$	Removal percentage of phosphorus at saturation time	%
rpm	Revolutions per minute	
SBG	Sugarcane baggase	
$SO_4^{2-}$	Sulfate ion	
$SeO_3^{2-}$	Selenite ion	
$t$	Service time of the column	min
$t_b$	Service time at breakthrough point	min
$t_s$	Service time at saturation point	min
TOC	Total organic carbon	mg/L
TSS	Total suspended solids	mg/L
$V_b$	Volume of water treated at breakthrough time	L
$V_e$	Volume of water treated at exhaustion time	L
$V_s$	Superficial velocity	cm/min
$VO_3^-$	Vanadate ion	
$Z$	Bed height	cm
$Z_o$	Critical bed depth	cm
$Zn^{2+}$	Zinc ion	
$Zr^{4+}$	Zirconium ion	
$ZrOCl_2 \cdot 8H_2O$	Zirconyl chloride octahydrate	
$\Delta G$	Change in Gibbs free energy	J/mol
$\Delta H$	Change in enthalpy	J/mol
$\Delta S$	Change in entropy	J/mol/K
\$	United States dollar	
€	Euro	

---

## ABBREVIATIONS

Symbol	Description
ATP	Adenosine tri phosphate
AWBs	Agricultural wastes/by-products
BDST	Bed depth service time
BET	Brunauer emmett teller
BSR	Batch stirred reactor
DNA	Deoxyribonucleic acid
FTIR	Fourier transform infrared spectroscopy
HAP	Hydroxyapatite
ILO	Iron loaded okara
ISSA	Incinerated sewage sludge ash
IZLO	Iron/zirconium loaded okara
MAP	Magnesium ammonium phosphate hexahydrate ( $\text{MgNH}_4\text{PO}_4 \cdot 6\text{H}_2\text{O}$ )
MBR	Membrane bioreactor
MTZ	Mass transfer zone
NOM	Natural organic matter
PAOs	Polyphosphate accumulating organisms
PBR	Packed bed reactor
PHB	Poly hydroxyl butyrate
ppm	Part per million
RNA	Ribonucleic acid
RO	Reverse osmosis
SEM-EDS	Scanning electron microscopy with X-ray microanalysis
TEM	Transmission electron microscope
USEPA	United States environmental protection agency

WWTP	Waste water treatment plant
XRD	Powder X-ray diffraction
ZLO	Zirconium loaded okara

## GREEK SYMBOLS

Symbol	Description	Unit
$\tau$	The time required for 50% phosphorus breakthrough	min
$\rho_b$	Bulk density of the adsorbent	$\text{g/cm}^3$
$\rho_p$	Particle density of the adsorbent	$\text{g/cm}^3$
$\rho_w$	Density of water	$\text{g/cm}^3$
$\eta$	Porosity of the adsorbent	%



## PhD DISSERTATION ABSTRACT

**Author:** THI AN HANG NGUYEN

**Date:** 26 June 2015

**Thesis title:** Removal and recovery of phosphorus from municipal wastewater by adsorption coupled with crystallization

**Statistical data:** 235 pages, 38 tables, 69 figures, and 185 references

**School:** Civil and Environmental Engineering

**Supervisors:** Prof. Dr. Huu Hao Ngo (Principal supervisor)  
Dr. Wenshan Guo (Alternative supervisor)  
Dr. Tien Vinh Nguyen (Co-supervisor)

**Keywords:** Phosphorus, Removal, Recovery, Adsorption, Crystallization, Struvite (MAP - Magnesium ammonium phosphate hexahydrate -  $\text{MgNH}_4\text{PO}_4 \cdot 6\text{H}_2\text{O}$ ), Municipal wastewater, Metal loading, Zirconium loaded okara (ZLO), Soybean by-product (okara), Agricultural by-product recycling

### Abstract:

Phosphorus is both critical and detrimental so it is desirable to develop a process that can not only remove but also recovery phosphorus. As the global phosphate reserve will be exhausted in 50-100 years, there is a need to explore alternatives to phosphate ores. Municipal wastewater is a significant source of phosphorus for recovery due to extremely high volumes and low levels of hazardous substances. This study investigates the feasibility of removing and recovering phosphorus from municipal wastewater by adsorption coupled with crystallization. Adsorbents were prepared from soybean by-product (okara) using metal loading method. The results indicated that zirconium loaded okara (ZLO) was the best among three developed adsorbents. The maximum adsorption capacity of ZLO was 58.93 mg  $\text{PO}_4/\text{g}$  adsorbent. The rapid adsorption was observed with 95% of the removal efficiency in 30 min. Isotherm data was best fitted by Freundlich model while kinetic data was satisfactorily described by Pseudo-second order model. Thermodynamic results revealed that the adsorption was feasible, spontaneous, and endothermic. The solution pH did not affect  $\text{PO}_4^{3-}$  uptake in a wide range of 2-11.  $\text{CO}_3^{2-}$  had a profound effect on  $\text{PO}_4^{3-}$  retention, whereas  $\text{SO}_4^{2-}$ ,  $\text{NO}_3^-$  and

Cl<sup>-</sup> were trivial inhibitors. Successful desorption and regeneration were achieved with 0.2 M NaOH and 0.1 M HCl, respectively. The ligand exchange was an important pathway for PO<sub>4</sub><sup>3-</sup> capture by ZLO. The column results showed that the highest dynamic adsorption capacity of ZLO was 50.35 mg PO<sub>4</sub>/g adsorbent. Thomas and Bed depth service time (BDST) models were most suitable for the description of the column adsorption behavior. ZLO column could be recycled at least three cycles with a reduction of 18.64% and 8.7% of adsorption capacity and adsorbent weight, respectively. A semi-pilot scale column packed with 100 g ZLO was capable of treating 132.5 L of municipal wastewater to meet the recommended discharge standard (1 mg P/L). The Zr<sup>4+</sup> detachment from ZLO during its operation was negligible. The struvite (MAP - Magnesium ammonium phosphate hexahydrate - MgNH<sub>4</sub>PO<sub>4</sub>·6H<sub>2</sub>O) recovery from desorption solution was most favored at pH 9, Mg: N: P molar ratio of 2:2:1, room temperature, using a combination of MgCl<sub>2</sub>·6H<sub>2</sub>O and NH<sub>4</sub>Cl. The harvested MAP was characterized by 93% MAP and 89% by mass P-bioavailability. Overall, the removal and recovery of phosphorus from municipal wastewater can be achieved by means of adsorption and crystallization. However, further study is necessary to make the process more economically viable.

## Graphical Abstract



